

Panel Display	Panel Size	15.4 inch	17.1 inch	18.5 inch
	Panel	A Grade	A Grade	A Grade
	Aspect ratio	16:9	16:9	16:9
	Contrast Ratio	100000:1	100000:1	100000:1
	Resolution	1280*800	1440*900	1366*768
	Brightness	300cd/m ²	300cd/m ²	300cd/m ²
	Response Time	2ms	2ms	2ms
	View Angle	H:160 °;V:140 °	H:160 °;V:140 °	H:160 °;V:140 °
	Pixel Configuration:	RGB Vertical Stripe	RGB Vertical Stripe	RGB Vertical Stripe
	Pixel Density:	98 PPI	98 PPI	98 PPI
	Aspect Ratio:	16:10 (H:V)	16:10 (H:V)	16:9 (H:V)
	Form Factor:	Flat Rectangle Display	Flat Rectangle Display	Flat Rectangle Display
	Pixel Pitch:	0.25875x0.25875 mm (HxV)	0.25875x0.25875 mm (HxV)	0.25875x0.25875 mm (HxV)
	Landscape or Portrait:	Landscape type	Landscape type	Landscape type
	Display Mode:	TN,Normally white,transmissive	TN,Normally white,transmissive	TN,Normally white,transmissive
	Display color:	262K (6-bit)	262K (6-bit)	262K (6-bit)
	Lamp Position:	Edge light type	Edge light type	Edge light type
	Lamp Type:	WLED	WLED	WLED
	Signal Category:	LVDS	LVDS	LVDS
	Signal Class:	LVDS(1 ch,6-bit)	LVDS(1 ch,6-bit)	LVDS(1 ch,6-bit)
Out Put	VGA(D-sub)	VGA	VGA	VGA
	HDMI1.4	optional	optional	optional
Else Feature	Color temperature	Warm/Code/Normal	Warm/Code/Normal	Warm/Code/Normal
	OSD language	Multi-languages	Multi-languages	Multi-languages
Appurtenance	Instruction	√	√	√
	Stand	√	√	√
Power	Built-in power	√	√	√
	Power supply	AC100-240V DC12V	AC100-240V DC12V	AC100-240V DC12V
	Rating power	10W	10W	14W
	Standby power	≤3W/≤1W	≤3W/≤1W	≤3W/≤1W
Packing	KA carton gift box	410*88*325	430*100*320	535*100*400
	master box (5 color boxes)	475*435*345	535*460*410	555*510*420
Weight	Gross Weight	1.8KGS	2.2KGS	3.5KGS
Loading	20GP	2200pcs	1800	1500pcs

	Size	15inch LED MONITOR	17inch LED MOINTOR	19inch LED MONITOR
Panel Display	Panel	A Grade	A Grade	A Grade
	Aspect ratio	4:3	4:3	4:3
	Contrast Ratio	1000:1	1000:1	1000:1
	Resolution	1024*768	1024*768	1280*1024
	Brightness	300cd/m ²	300cd/m ²	400cd/m ²
	Response Time	8ms	8ms	8ms
	View Angle	H:176°,V:176°	H:176°,V:176°	H:176°,V:176°
	VGA(D-Sub 15 pin)	√	√	√
	PC Audio	Optional	Optional	Optional
	earphone	Optional	Optional	Optional
	HDMI1.4	Optional	Optional	Optional
OSD Control		OSD control AUTO,+ ,POWER,-,MENU brightness,contrast ratio,auto adjustment,phase position,clock,Languages,function,		
Else Feature	Color temperature	Warm/Code/Normal	Warm/Code/Normal	Warm/Code/Normal
	OSD language	Multi-languages	Multi-languages	Multi-languages
	Zoom/16:9/4:3Mode	Zoom/Full screen	Zoom/Full screen	Zoom/Full screen
	still picture	Optional	Optional	Optional
Appurtenance	Instruction	√	√	√
	Stand	√	√	√
Power	External power	X	√	√
	Built-in power	√	X	X
	Plug	US/UK/south africa standard	US/UK/south africa standard	US/UK/south africa standard
	Power supply	AC100-240V DC12V	AC100-240V DC12V	AC100-240V DC12V
	Rating power	15W	15W	24W
	Standby power	≤3W/≤1W	≤3W/≤1W	≤3W/≤1W
Packing	color box size	405*105*435	530*100*388	575*102*420
Loading qty	20GP	1600	1300	1100
	40HQ	3300	3000	2700

	Size	21.5"
Panel Display	Panel	A Grade
	Aspect ratio	16:9
	Contrast Ratio	1000:1
	Resolution	1920*1080
	Brightness	400cd/m ²
	Response Time	8ms
	View Angle	H:176°,V:176°
	VGA(D-Sub 15 pin)	√
OSD Control		OSD control AUTO,+,POWER,-,MENU brightness,contrast ratio,auto adjustment,phase position,clock,Languages,function,
Else Feature	Color temperature	Warm/Code/Normal
	OSD language	Multi-languages
	Zoom/16:9/4:3Mode	Zoom/Full screen
Appurtenance	Instruction	√
	Stand	√
Power	External power	√
	Plug	Europe Standard
	Power supply	AC100-240V DC12V
	Rating power	20W
	Standby power	≤3W/≤1W
Packing	color box size	550*100*410
Loading qty	20GP	1100
	40HQ	3000

	Size	23.6"
Panel Display	Panel	A Grade TFT PANEL
	Aspect ratio	16:9
	Contrast Ratio	1000:1
	Resolution	1920*1080
	Brightness	400cd/m ²
	Response Time	8ms
	View Angle	H:176°,V:176°
	VGA(D-Sub 15 pin)	√
	PC Audio	Optional
	earphone	Optional
	HDMI1.4	Optional
OSD Control		OSD control AUTO,+,POWER,-,MENU brightness,contrast ratio,auto adjustment,phase position,clock,Languages,function,
Else Feature	Color temperature	Warm/Code/Normal
	OSD language	Multi-languages
	Zoom/16:9/4:3Mode	Zoom/Full screen
Appurtenance	Instruction	√
	Stand	√
Power	External power	√
	Plug	US/UK/south africa standard
	Power supply	AC100-240V DC12V
	Rating power	24W
	Standby power	≤3W/≤1W
Packing	color box size	550*100*410
Loading qty	20GP	1000
	40HQ	2500